



RS 125 - SPECIFICATII TEHNICE

TIP MOTOR	Mono- cilindru, 4-timpi, 4-valve, DOHC, racire lichid
DIMENSIUNE	58 x 47 mm
CAPACITATE CILINDRICA	124,2 cc
COMPRESIE	12.0~12.6 : 1
PUTEREA MAXIMA	11 kW at 10,000 rpm
CUPLUL MAXIM	11.2 Nm at 8,000 rpm
ELECTRONICA	ECU Electronic Magneti Marelli MIUG4 ø 32 mm
STARTER	Electric
LUBRIFICARE	Carter umed
Transmisie	6 viteze, rapoartele: 1° 11/33 - 2° 15/30 - 3° 18/27 - 4° 20/24 - 5° 25/27 - 6° 23/22
RAPORTUL PRIMAR	Raport: 29/69
RAPORTUL FINAL	Lant, 13/58
AMBREIAJ	Multi disc, umed
SUSPENSIE FATA	Upside-down de Ø 40 mm si 110 mm cursa
SUSPENSIE SPATE	Bascula asimetrica, amortizor monoshock cu cursa de 120 mm
FRANE	Fata: Ø 300 mm, otel, etrier cu 4 pistoane Spate: Ø 220 mm otel, etrier cu 1 piston Insertie metalica furtune frana
ABS	2 canale Bosch ABS cu sistem anti roll-over
ROTI	6 spite in aliaj usor
ANVELOPE	Fata: 100/80 - 17", spate: 140/70 – ZR 17
DIMENSIUNI	Lungime 1968 mm Latime 760 mm Inaltime 1,135 mm Inaltime sa 820 mm Ampatament 1,350 mm
Greutate	144 Kg (cu plinul de benzina)
Consum (WMTC)	2.6 l/100 km
Emisii CO2 (WMTC)	2.6 l/100 km 60 g/km EURO 5