

500X



SPECIFICATII TEHNICE

MOTOR

Tip	DOHC - 2 cilindri (paralel), 4 timpi
Capacitate cilindrica	471 cc
Diametru x Cursa	67 x 66.8 mm
Raport compresie	10.7 : 1
Putere maxima	47.6 CP / 8,600 rot/min
Cuplu maxim	43 Nm / 6,500 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Capacitate rezervor	17.5 litri (inclusiv rezerva)
Consum carburant (WMTC)	3.6 l / 100 km
Capacitate rezervor ulei	3.2 litri

EMISII CO2 & NORMA DE POLUARE

Norma poluare	Euro 5
Emisii Co2	82 g/km

SISTEM ELECTRIC

Demaror	Electric
Capacitate baterie	12V / 7.4AH
Lumini	LED
HISS (Honda Intelligent Security System)	Standard

TRANSMISIE

Tip	Manuala in 6 trepte
Ambreiaj	Multi-disc, umed, tip Slippery Clutch
Actionare ambreiaj	Mecanic, actionat prin cablu
Transmisie finala	Lant cu O-ring

DOTARI

Roata fata 19 inch
Furca telescopica USD - Showa Big Piston (SFF-BP) 41 mm
Iluminare Full LED
Assist / slipper clutch
Honda Intelligent Security System



SUSPENSIE & ROTI

Tip	Fata	Furca telescopica USD Showa Big Piston (SFF-BP), 41mm
	Spate	Mono-amortizor Prolink cu preincarcare ajustabila in 5 trepte
Jante	Fata	19M / C x MT 2.5
	Spate	17M / C x MT 4.5
Anvelope	Fata	110 / 80 R19 M/C
	Spate	160 / 60 R17 M/C

SISTEM DE FRÂNARE

Fata	Dublu Disc 296 x 4 mm, hidraulic, etrier radial Nissin, 4 pistoane, (*ABS)
Spate	Disc 240 x 5 mm, hidraulic, etrier doua pistoane, (*ABS)

CADRU

Tip	Diamond - Otel
Dimensiuni (L x l x î)	2.155 x 830 x 1.410 mm
Ampatament	1,445 mm
Unghi inclinare furca	27.5 °
Cursa	108 mm
Inaltime sa	830 mm
Garda la sol	180 mm
Masa proprie	199 kg