

CRF

300 RALLY



SPECIFICATII TEHNICE

MOTOR

Tip	DOHC - monocilindric răcit cu lichid
Capacitate cilindrica	286 cc
Diametru x Cursa	76 x 63 mm
Raport compresie	10.7 : 1
Putere maxima	27.3 CP / 8.500 rot/min
Cuplu maxim	26.6 Nm / 6.750 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Consum carburant	3.1 l/100 km
Capacitate rezervor carburant	12.8 l
Capacitate rezervor ulei	1.8 l

EMISII CO2 & NORMA DE POLUARE

Norma de poluare	Euro 5
Emisii CO2	73 g/km

SISTEM ELECTRIC

Sistem de aprindere	Gestionat electronic
Demaror	Electric

TRANSMISIE

Tip	MT 6 trepte
Ambreiaj	Umed multidisc
Transmisie finala	Lant cu O-ring

DOTARI

Euro 5
Slipper clutch
Ecran LCD
Faruri Led



SUSPENSIE & ROTI

Tip	Fata	Furca telescopica USD 43mm
	Spate	Prolink
Jante	Fata	Spite din aluminiu
	Spate	Spite din aluminiu
Anvelope	Fata	80/100-21M/C 51P
	Spate	120/80-18M/C 62P

SISTEM DE FRÂNARE

Fata	296mm x 3.5mm disc cu 2 pistoane
Spate	220 mm x 4.5mm disc cu un singur piston

CADRU

Tip	Oțel semi-dublu leagăn
Dimensiuni (L x l x î)	2.230 x 920 x 1.415 mm
Ampatament	1.455 mm
Unghi inclinare furcă	27.5°
Cursa	109 mm
Inaltime sa	885 mm
Garda la sol	275 mm
Masa proprie	153 kg