



SPECIFICATII TEHNICE

MOTOR

Tip	Monocilindru cu 2 supape, răcit cu aer
Capacitate cilindrica	125 cc
Diametru x Cursa	50 x 63.1
Raport compresie	10:01
Putere maxima	9,86 CP / 7.250 rot/min
Cuplu maxim	10.5 Nm / 5.500 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Capacitate rezervor	6.0
Consum carburant	1,52l / 100Km
Capacitate rezervor ulei	1,1 l

SISTEM ELECTRIC

Sistem de aprindere	Gestionat Electronic
Lumini	LED

TRANSMISIE

Tip	Lant
Ambreiaj	Ambreiaj umed, 5 trepte

EMISII CO2 & NORMA DE POLUARE

Norma de poluare	Euro 5
Emisii CO2	35 g/km

DOTARI

Lumini Full LED
Display Digital – LCD



CADRU

Tip	Otel
Dimensiuni (L x l x i)	1.760 x 720 x 1.015
Ampatament	1.200
Unghi inclinare furca	25°
Inaltime sa	761
Garda la sol	180
Masa totala	103

SUSPENSIE & ROTI

Tip	Fata	Furca frontala (31 mm)
	Spate	Mono shock, brat oscilant
Jante	Fata	Aluminiu turnat - 5 spite
	Spate	Aluminiu turnat - 5 spite
Anvelope	Fata	120/70-12
	Spate	130/70-12

SISTEM DE FRÂNARE

Fata	Disc 220 mm, etrier hidraulic cu dublu piston
Spate	Disc 190 mm, etrier hidraulic cu un singur piston