

NC750X



MOTOR

Tip	SOHC - 2 cilindri (linie), 4 timpi, 8 supape
Capacitate cilindrica	745 cc
Diametru x Cursa	77 x 80 mm
Raport compresie	10.7 : 1
Putere maxima	58 CP / 6.750 rot/min
Cuplu maxim	69 Nm / 4.750 rot/min

SISTEM DE ALIMENTARE

Tip	PGM-FI - Injectie electronica
Consum carburant	3.5 l/100 km
Capacitate rezervor carburant	14.1 l
Capacitate rezervor ulei	4 l

EMISII CO2 & NORMA DE POLUARE

Norma de poluare	Euro 5
Emisii CO2	82 g/km

SISTEM ELECTRIC

Sistem de aprindere	Gestionat electronic
Demaror	Electric
Lumini	LED

TRANSMISIE

Tip	MT / DCT 6 trepte
Ambreiaj	Umed multidisc / Hidraulic
Transmisie finala	Lant cu O-ring

DOTĂRI

Euro 5
Throttle By Wire (3 moduri de condus)
Honda Selectable Torque Control (HSTC)
Spatiu depozitare sub sa - 23 litri
Lumini LED

CULORI DISPONIBILE

MAT JEANS BLUE METALLIC



PEARL DEEP MUDGRY



MAT BALLISTIC BLACK METALLIC



CANDY CHROMOSPHERE RED



SUSPENSIE & ROTI

Tip	Fata	Furca telescopica (41 mm), cursa 120 mm
	Spate	Amortizor monoshock, brat oscilant Pro-Link, cursa 120 mm
Jante	Fata	17M/C x MT3.5
	Spate	17M/C x MT4.50
Anvelope	Fata	120/70-ZR17M/C (58W)
	Spate	160/60-ZR17M/C (69W)

SISTEM DE FRÂNARE

Fata	Disc 320 mm, hidraulic, etrier 2 pistoane (ABS)
Spate	Disc 240, hidraulic, etrier mono-piston (ABS)

CADRU

Tip	Diamant (otel)
Dimensiuni (L x l x i)	2.210 x 846 x 1.330 mm
Ampatament	MT: 1.525 mm / DCT: 1.535 mm
Unghi inclinare furcă	27°
Cursa	110 mm
Inaltime sa	800 mm
Garda la sol	145 mm
Masa proprie	MT: 214 kg / DCT: 224 kg