



GTS 125 I-GET – SPECIFICATII TEHNICE

MOTOR	HPE un cilindru, 4 timpi, 4 valve, cu system Start Stop, injectie electronica
ALEZAJ X CURSA	52mm x 58,7mm
CAPACITATE	125
PUTERE MAXIMA	10,3kW (14 HP) @ 8,750 rpm
CUPLU MAXIM	12 Nm @ 6,750 rpm
DISTRIBUTIE	Un arbore cu came (SOHC), 4 valve
SISTEMUL DE ALIMENTARE	Injectie nou PFI (Port Fuel Injection)
RACIREA	Lichid
UNGERE	Lichid
PORNIRE	Electrica
AMBREIAJ	Uscat, automatic centrifugal cu protectie de vibratie
TRANSMISIA	CVT cu convertitor de cuplu
CADRUL STRUCTURAL	Tabla de otel cu intaritari sudate
SUSPENSIA FATA	Brat unic cu arc si amortizor
SUSPENSIA SPATE	Doua amortizoare hidraulice cu functie preincarcare si ajustabile pe 4 pozitii
ROATA FATA	Aliaj aluminiu 3.00x12" – Tubeless 120/70-12"
ROATA SPATE	Aliaj aluminiu 3.00x12" – Tubeless 130/70-12"
DISC FRANA FATA	Otel inoxidabil , \varnothing 220 mm cu control hidraulic - ABS/ASR
DISC FRANA SPATE	Otel inoxidabil, \varnothing 220 mm cu control hidraulic - ABS/ASR
CAPACITATE REZERVOR	7 litrii (include rezerva de 2 litri)
LUNGIME/LATIME/AMPATAMENT/ INALTIME SA (MM)	1.980 / 765 / 1.380 / 790
NORMA DE POLUARE	EURO 5
CONSUM (KM/L)	38,5 KM/L
EMISSII (CO2)	59 G/KM