



MOTOR	Hpe, un cilindru, 4 timpi, 4 valve, injectie electronica
ALEZAJ	75 mm x 63 mm
CAPACITATE CILINDRICA	278cc
PUTERE MAXIMA	17.5 kW (23.8 HP) la 8,250 rpm
CUPLU MAXIM	26 Nm a 5,250 rpm
SISTEMUL DE ALIMENTARE	Sistem nou de injectie PFI (Port Fuel Injection)
PORNIRE	Electrica
TRANSMISIE	CVT
AMBREIAJ	Automatic uscat cu suportii antivibratie
RACIRE	Lichid
CAROSERIA	Tabla de otel sudata
SUSPENSIA FATA	Monobrat cu arc si amortizor
SUSPENSIA SPATE	Doua amortizoare cu setare preload pe 4 pozitii.
CONSUM (KM/L)	30.3 km/l
EMISII (CO2)	75 g/km
NORMA POLUARE	Euro 5
ROATA FATA	Tubeless 120/70 - 12"
ROATA SPATE	Tubeless 130/70 - 12"
FRANA FATA	Stainless steel, Ø 220 mm with hydraulic control - ABS/ASR
FRANA SPATE	Stainless steel, Ø 220 mm with hydraulic control - ABS/ASR
LUNGIME/LATIME/AMPATAMENT	1,975 / 775 / 1,375 mm
INALTIME SA	790 mm
REZERVOR	8.5 litrii (include 2 litrii rezerva)