

PACKAGE HIGHLIGHTS

- · Priced to excite
- · Designed for fun
- · Easy to ride
- $\cdot\,100\,000$ ways to make it your own

SPORT / FITT / ECO**

RYKER 900	
SHOWN WITH INTENSE	BLACK PANELS

	Rotax®600 ACE™	Rotax®900 ACE™		Rotax®
ENGINE			DIMENSIONS	
Туре	Rotax®600 ACE™ in-line 2 cylinders, liquid–cooled	Rotax®900 ACE™ in–line 3 cylinders, liquid–cooled with	LxW xH	2,352 x 1,! (92 . 6 x 5
	with electronic fuel injection and electronic	electronic fuel injection and electronic throttle control	Wheelbase	
	throttle control	electronic throttle control	Seat height	599 m
Bore & stroke	74 x 69,7 mm (2.9 x 2.7 in.)	74 x 69,7 mm (2.9 x 2.7 in.)	Ground clearance	
Power	50 hp (37.3 kW) @ 7300RPM	82 hp (61.1 kW) @ 8000RPM	Dry weight	2701
Torque	49.7 Nm (36.7 ft-lb) @ 6000RPM	79.1 Nm (58.3 ft-lb) @ 6500RPM	Type	_
CO2 emissions	127 g/km	143 g/km	Main Functions	Speedome
Fuel consumption	5.4 l/100 km (43.6 mpg)	6.08 l/100 km (38.7 mpg)		odometer to empty
TRANSMISSION				fuel gau
Туре	Automatic (CVT) v	vith reverse function	CAFETY & CECURITY	
CHASSIS			SAFETY & SECURITY	
Front suspension	Double	wishbone	SCS TCS	_
Front shocks type / travel		ver shocks / 136 mm(5.35 in.)	ABS	_
Rear suspension	Multi-link -m	nono swing arm	Anti-theft system	Digi
Rear shocks type / travel		hocks with preload adjustment / n (5.71 in.)	HHC	
Electronic brake distribution system	Foot-operated, hyd	draulic 3–wheel brake	COVERAGE	
Front brakes	270 mm discs with Nissi	n 2-pistonfloating calipers	Factory Warranty	
Rear brake	220 mm disc, 1–p	nistonfloating caliper	Roadside Assistance*	2-yearroad world le
Parking brake	Par	klock		world le
Front tires	MC 145,	/60R1666T		
Rear tire	MC 205,	/45R1677T	FEATURES	
Aluminum front rims	5-spokeCarbon black, 406 x 165 mm (16 x 6.5 in.)	10–spoke,Platinum silver, 406 x 114 mm (16 x 4.5 in.)		F
Aluminum rear rim	5-spokeCarbon black, 406 x 165 mm (16 x 6.5 in.)	10–spoke,Platinum silver, 406 x 165 mm (16 x 6.5 in.)		
CAPACITY				
Rider capacity		1		
Maximum vehicle load	204 kg (449.7 lb)			
Storage capacity	7 L (1.85 gal)			
Fuel capacity	20 L (5.28gal)		
Fuel Type	Premium unleaded			

	Rotax®600 ACE™	Rotax® 900 ACE™	
DIMENSIONS			
LxW xH	2,352 x 1,522 x 1,063 mm (92.6 x 59.9 x 41.9 in.)	2,352 x 1,522 x 1,060 mm (92.6 x 59.9 x 41.7 in.)	
Wheelbase	1,709 m	1,709 mm (67.3 in.)	
Seat height	599 mm (23.6 in.)	599 mm (23.6 in.) 597 mm (23.5 in.)	
Ground clearance	97 mm (3.8 in.)		
Dry weight	270 kg (594 lb)	280 kg (616 lb)	
INSTRUMENTATION			
ype 4.5"		gital display	
Main Functions	Speedometer, tachometer, odometer, trips, distance to empty, engine lights, fuel gauge and clock	Speedometer,tachometer, odometer,trips, distance to empty,engine lights, fuel gauge,clock, ECO mode andSport mode	
SAFETY & SECURITY			
SCS	Stability ControlSystem		
TCS	Traction Control System		
ABS	Anti–lockBraking System		
Anti-theft system	DigitallyEncoded Security System (D.E.S.S.™)		
HHC	Hill Hold Control		
COVERAGE			
Factory Warranty	2-yearBRP Li	2-yearBRP Limited Warranty	
Roadside Assistance*	2-yearroadside assistance provided by AllianzAssistance, world leader in Automotive and Travel assistance, on behalf of BRP.		
FEATURES			
	2 halogen headlamps (55–W) Front fenders with integrated LED lights Dual USB port Glove box		

Adaptive foamwaterproof seat

