## **MY24 OUTLANDER MAX XT-P 650 T ABS**



Protection

- •Tri-ModeDynamic Power Steering (DPS)

- Anti-Lock Braking System (ABS)
   Visco-4Lok front differential
   FOX† 1.5 PODIUM† QS3 shocks
   14 in. (35.6 cm) cast-aluminum beadlock wheels
   26 in. (66 cm) ITP Terracross radial tires
- •Heavy-duty front and rear bumpers
- •Painted plastics for premium look
- •3,500–lb (1,588 kg) winch •Aluminum taper–profile handlebar with full wrap handguards •7.6 in. wide digital display

Hyper Silver & Neo Yellow

ENGINE	650
Type	44 kW (59 hp), Rotax®650 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™)with Electronic Fuel Injection(EFI)
Transmission	CVT L/H/N/R/P
Drive Train	Selectable 2WD / 4WD / Lock 4WD modes with Brake Traction Control (BTC)
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
Power Steering	Tri-ModeDynamic Power Steering (DPS)
Speed Category	More than 60 km/h
SUSPENSIONS	
Front Suspension	Arched double A–armwith front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX† 1.5 PODIUM† QS3
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX† 1.5 PODIUM† QS3
TIRES / WHEELS	
Front & Rear Tires	ITP† Terracross 26 x8/10 x 14 in. (66 x 20.3 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast–aluminum beadlock
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-pistoncaliper

DIMENSIONS / CAPACITIES	650
Estimated Dry Weight *	890.6 lb (404 kg)
L xW xH	94 x 48 x 62.2 in. (238.8 x 121.9 x 158 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg) / Rear: 200 lb (90 kg)
Storage Capacity	5.7 gal (21.4 L)
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)
	7.6 in wide digital display
Gauge	7.6 in wide digital display DC outlet, 15–Aconnector
Gauge Instrumentation	
Gauge Instrumentation Ingnition	DC outlet, 15–Aconnector RF DigitallyEncoded Security System
Instrumentation Ingnition Lighting	DC outlet, 15–Aconnector  RF DigitallyEncoded Security System (D.E.S.S.™)
Gauge	DC outlet, 15-Aconnector  RF DigitallyEncoded Security System (D.E.S.S.™)  LED headlights
Gauge Instrumentation Ingnition Lighting Winch	DC outlet, 15–Aconnector  RF DigitallyEncoded Security System (D.E.S.S.™)  LED headlights  3,500–lb(1,588 kg) winch  Towing hitch with trailer plug, directional

wrap handguards

Heavy–duty front & rear bumpers Mudguards