## **MY24 OUTLANDER PRO XU HD5**



## Tundra Green

## PACKAGE HIGHLIGHTS

- •Tri-Mode Dynamic Power Steering (DPS)
- •Speed Limiter

Winch

Handlebar

Protection

Seat

- •Intelligent Engine Braking (iEB™)
- •Visco-4Lok† front differential
- •26 in. (66 cm) XPS Trail King tires with 12 in. (30.5 cm) cast-aluminium wheels
- •Premium Front Bumper, Rear Bumper, Full skid plate
- •Premium Gloveboxwith cellphone holder and USB charger

ENGINE	HD5
Type	30 kW (40 hp) / 37 lb-ft,Rotax®ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT with work calibration Extra low L/H/N/R/P
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco–4Lok† front differential
Driving Assistance	IntelligentEngine Braking(iEB™) Speed limiter
Power Steering	Tri-ModeDynamic Power Steering (DPS)
Speed Category	Over 60 km/h
SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A–arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube
TIRES & WHEELS	
Front & Rear Tires	XPS Trail King, 6–plyrating, 26 x 8/10 x 12 in. (66 x 20.3 / 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin–pistoncalipers
Rear	Single 214mm disc brake with hydraulic twin–pistoncaliper

DIMENSIONS & CAPACITIES	
Estimated Dry Weight*	816 lb (370.1 kg)
L xW xH	89.9 x 48.8 x 48.2 in. (228.4 x 123.9 x 122.5 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	38.6 in. (98 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg) trailer with brake 870 lb (394 kg) without brakes
Fuel Capacity	5.1 gal (19.5 L)
FEATURES	
Gauge	4.5 in. digital display
Instrumentation	USB phonecharger
Ignition	RF DigitallyEncoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights

Premium front bumper, rear bumper, full skid plate

N/A

Standard

Standard