## MY24 OUTLANDER MAX DPS 700 T ABS



## PACKAGE HIGHLIGHTS

- •Tri-Mode Dynamic Power Steering (DPS)
- •Anti-lock Braking System (ABS)
- •Work / Standard / Sport modes
- •Visco-Lok† QE auto-locking front differential
- •Full skid plate
- Tow ball
- •Horn, flashers and mirrors

ENGINE	700
Туре	37 kW (50 hp) / 41 lb–ft,Rotax®ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC $^{\text{TM}}$ ) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT L/H/N/R/P
Drive Train	Selectable 2WD / 4WD Visco–Lok†ABS (Open differential) with BTC (Brake torque Control)
Driving Assistance	Work / Standard / Sport modes
Power Steering	Tri-ModeDynamic Power Steering (DPS)
Speed Category	More than 60 km/h
SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube
TIRES & WHEELS	
Front & Rear Tires	25 x 8/10 x 12 in. (63.5 x 20.3 / 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast–aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin–pistoncalipers
Rear	Single 214 mm disc brake with hydraulic twin–pistoncaliper

## **DIMENSIONS & CAPACITIES**

Weight*	802.6 lb (364.1 kg)
L xW xH	94.2 x 47.6 x 56.9 in. (239.2 x 120.9 x 144.6 cm)
Wheelbase	60.4 in. (153.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38.6 in. (98 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg) trailer with brake 870 lb (394 kg) without brakes
Fuel Capacity	5.1 gal (19.5 L)

## **FEATURES**

Gauge	4.5 in. digital display
Instrumentation	N/A
Ignition	RF DigitallyEncoded Security System (D.E.S.S.™)
Lighting	LED headlights and taillights LED signature
Winch	N/A
Seat	Standard
Handlebar	Standard
Protection	Full skid plate