

MY24 MAVERICK MAX X RS TURBO RR WITH SMART-SHOX



 Fiery Red & Hyper Silver

ENGINE

Type	149 kW (200 hp*), Rotax®ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 2WD/4WD with front diff, lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Double A-arm with sway bar / 22 in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 22 in. (55.9 cm) travel
Rear Shocks	FOX† 3.0 PODIUM† remote reservoir with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)

TIRES / WHEELS

Front & Rear Tires	Maxxis Carnivore† 32 x 10 / 10 x 14 in. (81.3 x 25.4 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

HIGHLIGHTS

- Smart-Lok™ front differential
- Smart-Shox Technology featuring DDA Valve
- FOX† 3.0 PODIUM† shocks with bypass
- Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- X-package graphics/seats
- 4-point harness with shoulder pads
- Can-Am LED signature
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 32 in. (81.3 cm) Maxxis Carnivore† tires
- Full roof
- HMWPE full skid plate
- Horn & Buzzer

DIMENSIONS / CAPACITIES

Estimated Dry Weight **	1,942 lb (880.9 kg)
Chassis / Cage	Dual-phase 980 steel
L x W x H	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC Outlet (10-A)
Magneto	850 W
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

*149kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.