



SR GT 200 - TECHNICAL SPECIFICATIONS

Engine	Single-cylinder 4-stroke i-get with Start&Stop system
Engine capacity	61.5 mm x 58.7 mm
Bore x stroke	174 cc
Max. power	13 kW at 8,500 rpm
Max. Torque	16.5 Nm at 7,000 rpm
Consumption	2,6 l/100 km
CO2 Emissions	61 g/km
Valve timing system	Single overhead camshaft, 4 valves
Cooling	Liquid
Fuel system	Electronic injection
Lubrication	Wet sump
Starter	Electric
Transmission	Continuously variable transmission (CVT)
Clutch	Automatic centrifugal dry clutch
Chassis	Double cradle, in high-resistance steel tubing
Front suspension	Hydraulic telescopic fork \varnothing 33 mm (120 mm travel)
Rear suspension	Double hydraulic shock absorber with adjustable preload (102 mm travel)
Front brake	Hydraulic with wave disc, \varnothing 260 mm - ABS
Rear brake	Hydraulic with wave disc, \varnothing 220 mm
Front tyre	Tubless 110/80 - 14"
Rear tyre	Tubless 130/70 - 13"
Length	1.920 mm
Width	765 mm
Seat height	799 mm
Wheelbase	1.350 mm
Fuel tank capacity	9 L
Emissions compliance	EURO 5