



2024 CRF300L RALLY SPECIFICATIONS*

Engine Type 286cc liquid-cooled single-cylinder four-stroke

Bore And Stroke 76.0mm x 63.0mm

Compression Ratio 10.7:1

Valve Train DOHC; four valves per cylinder

Induction Programmed Fuel Injection (PGM-FI); 38mm throttle body

DRIVE TRAIN

ENGINE

Transmission Six-speed

Final Drive #520 chain; 14T/40T

CHASSIS SUSPENSION BRAKES

Front Suspension 43mm inverted fork; 10.2-inch travel

Rear Suspension Pro-Link® single shock with adjustable spring preload; 10.2-inch travel

Front Brake Single 296mm disc with twin-piston caliper

Rear Brake Single 220mm disc
Front Tire IRC GP21 80/100-21
Rear Tire IRC GP 22 120/80-18

DIMENSIONS

Rake 27.5°
Trail 4.3 inches
Wheelbase 57.2 inches
Seat Height 35.2 inches
Ground Clearance 10.9 inches

Curb Weight 331 pounds

Fuel Capacity 3.4 gallons, including 0.6-gallon reserve

OTHER

Available Colors Red

Model ID CRF300LR

FACTORY WARRANTY INFORMATION

One Year Included Transferable, unlimited mileage limited warranty

Optional Extended Extended coverage available with a HondaCare® Protection Plan