



SPRINT -PRIMAVERA 50 4T3V – SPECIFICATII TEHNICE

MOTOR	3-valve 4-timpi mono cilindru i-get catalizator
CAPACITATE	49 cc
CURSA X ALEZAJ	39 mm x 41,4 mm
PUTERE MAXIMA LA ARBORELE COTIT	2.2 kW - 3 HP - at 7,500 rpm
CUPLU MAXIM	2.9 Nm at 7,000 rpm
CONSUM	40 km/l
NORME EMISII CO2	57 g/km
SISTEM ALIMENTARE	Injectie electronica
RACIRE	Aer
PORNIRE	Electric
CUTIE VITEZA	CVT automatica cu servocuplu
AMBREIAJ	Automat centrifugal uscat cu amortizoare de soc
STRUCTURA CAROSERIE	Caroserie tabla otel cu structura armaturi sudate
SUSPENSIE FATA	Mono brat cu arc elicoidal și amortizor hidraulic
SUSPENSIA SPATE	Amortizor hidraulic cu arc elicoidal reglabil preincarcare 4 poziții
FRANA FATA	Disc otel Ø 220 mm cu actionata hidraulic
FRANA SPATE	Tambur Ø 140 mm actionata mecanic
SISTEM ABS/ASR	-
ANVELOPA FATA	Tubeless 110/70 - 12"
ANVELOPA SPATE	Tubeless 120/70 - 12"
LUNGIME/LATIME/DISTANTA INTRE ROTI	1,870 / 735 / 1,330 mm
INALTIME SA	790 mm
CAPACITATE REZERVOR	7,5 litri
NORME EMISII	Euro 5