



SR GT 125 - TECHNICAL SPECIFICATION

Engine	Single-cylinder 4-stroke i-get with Start & Stop system
Engine capacity	125 cc
Bore x stroke	52 mm x 58.7 mm
Max. power	11 kW @ 8,900 rpm
Max. Torque	12 Nm @ 6,750 rpm
Consumption	2.5 l/100 km
CO2 Emissions	60 g/km
Valve timing system	Single overhead camshaft, 4 valves
Cooling	Liquid
Fuel system	Electronic injection
Lubrication	Wet sump
Starter	Electric
Transmission	Continuously variable transmission (CVT)
Clutch	Automatic centrifugal dry clutch
Chassis	Double cradle, in high-resistance steel tubing
Front suspension	Hydraulic telescopic fork \varnothing 33 mm (120 mm travel)
Rear suspension	Double hydraulic shock absorber with adjustable preload (102 mm travel)
Front brake	Hydraulic with wave disc \varnothing 260 mm ABS
Rear brake	Hydraulic with wave disc \varnothing 220 mm
Front tyre	110/80 - 14"
Rear tyre	130/70 - 13"
Length	1,920 mm
Width	765 mm
Seat height	799 mm
Wheelbase	1,350 mm
Fuel tank capacity	9 litres
Emissions compliance	EURO 5+