

## **MEDLEY 125 S – TECHNICAL SPECIFICATIONS**

MOTOR	Single cylinder, 4-stroke Piaggio i-get with 'Start & Stop' system
ENGINE CAPACITY	125 cc
BORE X STROKE	52 mm / 58.7 mm
MAX POWER	11 kW at 8.750 rpm
MAX TORQUE	12 Nm at 6500 rpm
DISTRIBUTION	Single overhead camshaft (SOHC) - 4 valves
COOLING	Liquid
FUEL SYSTEM	Electronic injection
LUBRICATION	Wet sump
STARTER	Electrical
TRANSMISSION	Automatic continuously variable transmission (CVT) with
CLUTCH	torque server Automatic centrifugal dry clutch
FRAME	Single cradle structure in tubular steel with pressed
FRONT SUSPENSION	reinforcements Telescopic hydraulic fork
REAR SUSPENSION	Hydraulic dual action shock absorber, 5-position spring
BRAKING SYSTEM	preload adjustment Bosch two-channel ABS 10.0
FRONT BRAKE	Ø 260mm brake disc served by Ø 25,4 mm dual piston
	floating calliper
REAR BRAKE	Ø 240mm brake disc served by Ø 22 mm dual piston floating calliper
FRONT TYRE	Tubeless 100/80-16"
REAR TYRE	Tubeless 120/70-14"
SEAT HEIGHT	799 mm
WHEELBASE	1,395 mm
DRY WEIGHT	136 Kg
FUEL TANK CAPACITY	7 litres (including 1.5 litre reserve)
CONSUMPTION (WMTC CYCLE)	42 km/l
CO2 EMISSIONS	59 g/km
EMISSIONS COMPLIANCE	Euro 5