



2016 Bearcat 3000 LT



AVAILABLE COLORS



Blue

Engine Specifications

Type	4-stroke
Displacement	700cc
Cooling	Liquid
Cylinders	2
Bore x Stroke	76.9 x 75.3 mm
Lubrication	Wet sump
Ignition	3D with throttle position sensor
Fuel Delivery	Electronic Fuel Injected (EFI)
Exhaust	2-into-1 stainless steel pipe with stainless steel muffler
Fuel Capacity	10.7 gal.
Minimum Octane	87

Suspension Specifications

Front Suspension	Arctic Race Suspension
Ski Shocks	Arctic Cat IFP
Front Travel	9.5 in.
Rear Suspension	SLIDE-ACTION Rear Suspension, coupling blocks, Torque-Sensing Link rear arm, adjustable torsion springs
Front Track Shock	Arctic Cat Gas IFP
Rear Track Shock	Arctic Cat Gas IFP
Rear Travel	13.5 in.

Dimensions Specifications

Overall Length	130 in.
Overall Width	49 in.
Track Type	Cobra
Track Width	15 in.
Track Length	146 in.
Lug	1.35 in.
Pitch	2.86 in.
Ski Stance	35.5-41.5 in. Adjustable
Ski Type / Width	ProUte - 10/8
Runner Type	Dual split runner w/carbide

Instrumentation Specifications

Type of Gauge	Power Sport
Speedometer	Digital
Tachometer	Digital
Odometer	Digital
Fuel	Digital
Oil	Indicator Light
Coolant	Indicator Light
Clock	Digital
Battery Voltage	Digital
Hours	Digital

Feature Specifications

12V Outlet	Standard
Auxiliary Gas Tank 4.3 gal.	Accessory
Electric Start	Standard
Front Bumper	Sport
Goggle Holder	Accessory
Hand & Thumb Warmers	Standard
Headlights	Dual halogen 2-bulb
Ice Scratchers	Accessory
Locking Detachable Storage Cases	Accessory
Mirrors	Accessory
Mountain Strap	Standard
Passenger Footrests	Accessory
Passenger Seat	Accessory
Radiator	Standard
Rear Rack	Standard
Rear Storage	Tunnel Bag
Seat	Mountain
Sno Pro Brake Lever	Accessory
Steering	Adjustable mountain handlebar
Tether Switch	Accessory
Tow Hitch	Pivot
Visor Plug-ins	Accessory
Windshield	17" High-height

Powertrain Specifications

Drive Clutch	Arctic 6 post (rpm sensing)
Driven Clutch	10.4 in. dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Race radial master cylinder hydraulic brake
Clutch Calibration	0-5,000 ft.
Gearing	19/50
Reverse	Push-button

Specifications Subject To Change

All rights reserved. Cobra,™ Hacksaw™ and Ripsaw™ are trademarks of Camoplast Inc. Diamond Direct Drive™ is a trademark of Black Diamond, Inc. FOX EVOL,™ FOX FLOAT™ and FOX Zero Pro are registered trademarks of FOX Racing Shox. ACT™ Arctic Cat, Arctic Drive System,™ Arctic Race Suspension,™ ARS,™ AWS,™ Bearcat, C-TEC2,™ C-TEC4,™ CatMaster, Cat to the Core,™ Cross Country,™ El Tigré, FasTrack, High Country,™ Lynx, Pantera, Power Claw,™ ProClimb,™ ProCross,™ ProTour,™ RIDEMORE,™ Share Our Passion,™ Slide-Action Rear Suspension,™ Sno Pro, SpeedRack, Torque Control Link,™ Twin Spar,™ World's Fastest Snowmobiles,™ XT,™ Z1™ and ZR are trademarks or registered trademarks of Arctic Cat Inc. Arctic Cat Sales Inc. is not a successor of Arctic Enterprises, Inc. ©2014 Arctic Cat Sales Inc., 601 Brooks Avenue South, Thief River Falls, MN 56701.

At Arctic Cat, we're always improving our snowmobiles to provide the best performance and experience. That's why the specifications for 2015 model Arctic Cat snowmobiles are subject to change without notice. See your dealer for details.

*MSRP excludes tax, license, registration, destination charge of \$400 and dealer setup. Dealer prices may vary.